



Accumpump technology
Superior Performance
Low Cost of Ownership

EXPERIENCE WEILER® GRINDING

Superior product definition and texture starts with VersaGrind®

VersaGrind Pump Grinding Systems bring unprecedented performance and particle definition to sausage production, as well as other applications where high product quality and distinctive appearance is of critical importance. Exclusive to Provisur is proprietary AccuPump® technology that provides the versatility to produce a wide range of product textures with exceptional definition and uniformity.

- Delivers consistent and repeatable results from a wide range of raw materials
- Dominator Technology for optimal product flow efficiency and product quality
- Particularly well suited for high definition sausage and highly viscous products
- Superior product definition
- Versatile range of textures



PROVISUR
TECHNOLOGIES

Pushing Boundaries®

Count on the VersaGrind® Pump Grinding Systems for Superior Product Quality and Texture.

With its independent knife speed and proven AccuPump technology, the Weiler® VersaGrind 11 Pump Grinding System allows processors the flexibility to vary product texture as it is ground out of the plate for superior product definition and uniformity. It's ideal for sausage and other meat blends.

Benefits:

1. AccuPump Technology
2. Dominator Technology
3. Rotating Base

Raw Materials:

- Sausage Blends
- Fresh Pork
- Fresh Beef
- Fresh Poultry



Features:

- AccuPump technology
- Superior versatility
- Highest quality finished products
- High grinding capacity
- Stainless-steel construction
- Dominator® cutting parts and bone collection technology
- Independent grinder and pump for orientation versatility
- Spring-loaded knife holders
- Low maintenance and ownership costs
- CE Compliant
- Positive displacement pump
- Anti-bridging paddle
- Variable frequency drive on unload screw, pump and knife
- Right or left hand pump configuration
- 4" (101mm) or 6" (152mm) pump

Options:

- Tilttable head assembly
- Swivel base
- Jacketed pipe
- Water heater

MODEL	PLATE DIAMETER INCHES (MM)	HOPPER CAPACITY CUBIC FT. (LITERS)	PUMP SIZE INCHES (MM)	GRINDER HP (KW)	PUMP HP (KW)	SCREW HP (KW)	AGITATOR HP (KW)	GRIND RATE HR LBS (KG)
4" VersaGrind 11	11 (279)	42 (1190)	4 (101)	30 (22)	20 (15)	7.5 (5.5)	2 (1.5)	30,000 (13,607)
6" VersaGrind 11	11 (279)	42 (1190)	6 (152)	40 (29)	20 (15)	7.5 (5.5)	2 (1.5)	39,000 (17,690)

* Actual grind rate will depend on application specification, including but not limited to reduction size, raw material, and raw material temperature.

* Different hopper capacities are available upon request and review by factory

To learn more, visit <https://www.provisur.com/en/equipment/grinding-and-mixing/versagrind-pump-grinders/>

